

DIODES AND RECTIFIERS

GENERAL PURPOSE DIODES RATINGS @ 25°C

Catalog Number	PIV (min) V	If A	I _r (max) @ V _r μA	V _f (max) @ I _f V	Case Style
276-1101	50	1.000	10	1.6	DO41
276-1102	200	1.000	10	1.6	DO41
276-1103	400	1.000	10	1.6	DO41
276-1104	600	1.000	10	1.6	DO41
276-1114	1000	2.500	200	1.0	A1vm
276-1122	75	0.010	250nA	1.0	A1
276-1123*	60	0.085	15	1.0	A1
276-1141	50	3.000	500	1.2	A3q
276-1143	200	3.000	500	1.2	A3q
276-1144	400	3.000	500	1.2	A3q

*GERMANIUM

ZENER DIODES—1 Watt

Catalog Number	V _z Volts ±10%	I _z @ mA	Z _z @ I _z ohms max	Case Style
276-565	5.1	49	7	DO41
276-561	6.2	41	2	DO41
276-562	9.1	25	7	DO41
276-563	12.0	21	9	DO41
276-564	15.0	17	14	DO41

BRIDGE RECTIFIERS

Catalog Number	PIV (min) V	I _f (max) A	Case Style
276-1146	50	4	M532a
276-1152	100	1.4	M548
276-1161	50	1	Y1
276-1171	100	4	M532a
276-1173	400	4	M532a
276-1181	250	6	M532a
276-1185	50	25	—